

IEC EN 60598-1 RG 1	UK CA		IP20 ↑ IP43	halogen	IK03		CE			850°C	T _a 5 25	
---------------------------	----------	--	----------------	---------	------	--	----	--	--	-------	------------------------	--

Cetus3


A low height, recessed LED downlight. Suitable for ceiling cut-outs Ø145-180 mm for easy refurbishments or fast initial installations. Remote, pluggable, Fixed output LED driver with 3 hour, Self/DALI Addressable test, emergency lighting circuit. Body: die-cast aluminium for thermal management. Diffuser: polycarbonate, smooth reflector in white finish with wide beam. Reflector and trim: high quality, highly reflective polycarbonate. Class II electrical (this product is not earthed), IP43_IP20. Spring clips suitable for ceiling thicknesses from 1 to 35 mm.

For installation in concrete ceilings please contact sales. Equipped with LCS technology, with two lumen outputs (2000lm and 3400lm) and three colour temperatures (3000K, 3500K and 4000K) selectable from below by a rotary switch. Pre-set to 4000K, high luminous flux.

Dimensions: Ø195 x 100 mm
 Luminaire input power: 25.4 W
 Luminaire luminous flux: 3221 lm
 Luminaire efficacy: 127 lm/W
 Weight: 1.09 kg



TLG_CTU3_F_M_LED_RWH_Persp.jpg



TLG_CTU3_M_HFM.wmf

This product contains a light source of energy efficiency class D.

Cetus3

92943861 CETUS3 M LCS HF E3D RWH

THORN