

Novaline Style

THORN

96635523 NOVS M 2500-830 DI HFI WH

| | | | | | | | | | | | | | | |
|------------------------|------|----------|----|------|---|---------|------|--|----|--|--|-------|---------------------------|--|
| IEC EN 60598-1 RG 1 | RoHS | UK CA | 11 | IP54 | D | halogen | IK08 | | CE | | | 850°C | T _a -15 +25 | |
|------------------------|------|----------|----|------|---|---------|------|--|----|--|--|-------|---------------------------|--|

Novaline Style

Decorative circular luminaire with medium body. Low indirect component for wall and ceiling illumination. Electronic, DALI dimmable. Aesthetic trim of the luminaire made of polycarbonate in white. Diffuser: opal polycarbonate. Class II electrical (this product is not earthed), IP54. Complete with 3000K LED.

Dimensions: Ø397 x 69 mm
Luminaire input power: 17.6 W
Luminaire luminous flux: 2300 lm
Luminaire efficacy: 131 lm/W
Weight: 2.14 kg



TLG_NOVS_F_4WH.jpg



TLG_NOVS_M_LD400.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

Novaline Style

96635523 NOVS M 2500-830 DI HFI WH

THORN