

Punch

96636035 PUNCH 3 LRO MSP 5500-940 L12 HF

| | | | | | | | | |
|----------|------|------|---|----|--|--|-------|-------------------------|
| UK CA | IP20 | IK03 | ⊕ | CE | | | 650°C | T _a 0 +25 |
|----------|------|------|---|----|--|--|-------|-------------------------|

Punch

A slim, suspended luminaire with direct/indirect distribution. fixed output control gear Electronic,. Body: steel sheet, powder coated white (close to RAL9016). Endcaps: steel sheet powder coated white (close to RAL9016). Light guided via backlit multilayer PMMA LRO luminance reducing optic with UGR <19, closed optical system to prevent damage from electrostatic discharge, ideal for schools and offices. Class I electrical, IP20, Impact strength: IK03. Electrical connection via piano key terminal block. Complete with 4000K LED.

Y-Suspension connector included - Suspension cord with ceiling rose to be ordered separately (22171581).

Dimensions: 1262 x 162 x 50 mm

Luminaire input power: 48.9 W

Luminaire luminous flux: 5371 lm

Luminaire efficacy: 110 lm/W

Weight: 3.5 kg



TLG_PNCH_F_LRO_suspended_on_PDB.jpg



TLG_PNC3_M_PLEXD.wmf

This product contains light sources of energy efficiency class D.