

## Punch

96636043 PUNCH 3 LRO MSC 3200-830 L12 HF

|          |      |      |   |    |  |  |       |                         |
|----------|------|------|---|----|--|--|-------|-------------------------|
| UK<br>CA | IP20 | IK03 | ⊕ | CE |  |  | 650°C | T <sub>a</sub> 0<br>+25 |
|----------|------|------|---|----|--|--|-------|-------------------------|

### Punch

A slim, surface mounted luminaire with direct distribution. fixed output control gear Electronic,. Body: steel sheet, powder coated white (close to RAL9016). Endcaps: steel sheet powder coated white (close to RAL9016). Light guided via backlit multilayer PMMA LRO luminance reducing optic with UGR <19, closed optical system to prevent damage from electrostatic discharge, ideal for schools and offices. Class I electrical, IP20, Impact strength: IK03. Electrical connection via piano key terminal block. Complete with 3000K LED.

Can be used as a suspended direct only luminaire when combined with Y-Suspension connector and suspension kit (to be ordered separately 22171581 & 22171349).

Dimensions: 1262 x 162 x 50 mm  
 Luminaire input power: 23.1 W  
 Luminaire luminous flux: 3011 lm  
 Luminaire efficacy: 130 lm/W  
 Weight: 3.5 kg



TLG\_PNCH\_F\_LRO\_surface\_on\_PDB.jpg



TLG\_PNC3\_M\_PLEXD.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

# Punch

96636043 PUNCH 3 LRO MSC 3200-830 L12 HF

THORN