

# Punch

THORN

96636051 PUNCH 3 LRO MSP 6600-930 L15 HFIX E3

|          |      |      |   |    |   |   |       |                         |  |
|----------|------|------|---|----|---|---|-------|-------------------------|--|
| UK<br>CA | IP20 | IK03 | ⊕ | CE |  |  | 650°C | T <sub>a</sub> 0<br>+25 |  |
|----------|------|------|---|----|---|---|-------|-------------------------|--|

## Punch

A slim, suspended luminaire with direct/indirect distribution. DALI dimmable Electronic, with 3 hour, manual test, emergency lighting circuit. Body: steel sheet, powder coated white (close to RAL9016). Endcaps: steel sheet powder coated white (close to RAL9016). Light guided via backlit multilayer PMMA LRO luminance reducing optic with UGR <19, closed optical system to prevent damage from electrostatic discharge, ideal for schools and offices. Class I electrical, IP20, Impact strength: IK03. Electrical connection via pre-installed power cord (2.5m). Complete with 3000K LED.

Y-Suspension connector included - Suspension cord with ceiling rose to be ordered separately (22171581).

Dimensions: 1542 x 162 x 50 mm  
Luminaire input power: 63.4 W  
Luminaire luminous flux: 6759 lm  
Luminaire efficacy: 107 lm/W  
Weight: 3.8 kg



TLG\_PNCH\_F\_LRO\_suspended\_on\_PDB.jpg



TLG\_PNC3\_M\_PLEXD.wmf

This product contains light sources of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting