

# Punch

# THORN

## 96636057 PUNCH 3 ASYM MSP 2200-930 L12 HF



### Punch


A slim, suspended luminaire with asymmetrical distribution. fixed output control gear Electronic,. Body: steel sheet, powder coated white (close to RAL9016). Endcaps: steel sheet powder coated white (close to RAL9016). Louvre: glossy aluminium,. Class I electrical, IP20, Impact strength: IK03. Electrical connection via pre-installed power cord (2.5m). Complete with 3000K LED. Suspension kit to be ordered separately

Y-Suspension connector included - Suspension cord with ceiling rose to be ordered separately (22171581).

Dimensions: 1180 x 116 x 44 mm  
Luminaire input power: 16 W  
Luminaire luminous flux: 2000 lm  
Luminaire efficacy: 125 lm/W  
Weight: 3.5 kg



TLG\_PNCH\_F\_ASYM.jpg



TLG\_PNC3\_M\_LDASY.wmf

This product contains a light source of energy efficiency class E.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement. © Thorn Lighting

# Punch

96636057 PUNCH 3 ASYM MSP 2200-930 L12 HF

THORN