

Novaline Style

92974716 NOVS S 1900-840 D MWS WH

IEC EN 60598-1 RG 1	RoHS	UK CA	IP54		halogen	IK08		CE			850°C	T _a -15 +25
---------------------------	------	----------	------	--	---------	------	--	----	--	--	-------	---------------------------

Novaline Style

Decorative circular luminaire with small body and direct light distribution.. Electronic, Integral presence detector for on/off control. Aesthetic trim of the luminaire made of polycarbonate in white. Diffuser: opal polycarbonate. Class II electrical (this product is not earthed), IP54. Complete with 4000K LED.

Dimensions: Ø320 x 69 mm
 Luminaire input power: 13.7 W
 Luminaire luminous flux: 1900 lm
 Luminaire efficacy: 139 lm/W
 Weight: 1.7 kg



TLG_NOVS_F_3WH.jpg



TLG_NOVS_M_LD300.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Novaline Style

92974716 NOVS S 1900-840 D MWS WH

THORN