

Novaline Style

92981926 NOVS M 3500-840 D HFI E3D SR

IEC EN 60598-1 RG 1	RoHS	UK CA	11	IP54	D	halogen	IK08		CE			850°C	T _a -15 +25
---------------------------	------	----------	----	------	---	---------	------	--	----	--	--	-------	---------------------------


Novaline Style

Decorative circular luminaire with medium body and direct light distribution.. Electronic, DALI dimmable with 3 hour, Self/DALI Addressable test, emergency lighting circuit. Aesthetic trim of the luminaire made of polycarbonate in silver. Diffuser: opal polycarbonate. Class II electrical (this product is not earthed), IP54. Complete with 4000K LED.

Dimensions: Ø397 x 69 mm
 Luminaire input power: 24.6 W
 Luminaire luminous flux: 3500 lm
 Luminaire efficacy: 142 lm/W
 Weight: 2.42 kg



TLG_NOVS_F_4SR.jpg



TLG_NOVS_M_LD400.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Novaline Style

92981926 NOVS M 3500-840 D HFI E3D SR

THORN