


## 92984179 FORCELED 4000 840 HFI QC5TW



### ForceLED

A compact IP66, dust and moisture proof LED luminaire. Electronic, DALI dimmable control gear. Class I electrical, IK10. Canopy: fully recyclable aluminium painted white. Diffuser: UV stabilised polycarbonate with linear prisms. Toggles: stainless steel. For surface, BESA or suspended mounting. Quick-fix brackets supplied for surface mounting. Mounting kits for conduit, chain suspension and catenary suspension are available as accessories. Equipped with 5 pole Quick Connect sockets though wired. Complete with 4000K LED.

ambient temperature: -20°C to +50°C

Dimensions: 735 x 180 x 95 mm  
 Luminaire input power: 26.1 W  
 Luminaire luminous flux: 4000 lm  
 Luminaire efficacy: 153 lm/W  
 Weight: 3.3 kg



TLG\_FORL\_F\_PDBUNLIT.jpg



TLG\_FORL\_M\_LED.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.