








92984182 FORCELED 4000 840 BC

	IP66			IK10					850°C	T _a -20 +45	
---	------	---	---	------	---	---	---	---	-------	---------------------------	--

ForceLED

A compact IP66, dust and moisture proof LED luminaire. Electronic. Wireless controlled via App with Bluetooth® 4.x - basicDIM Wireless. Class I electrical, IK10. Canopy: fully recyclable aluminium painted white. Diffuser: UV stabilised polycarbonate with linear prisms. Toggles: stainless steel. For surface, BESA or suspended mounting. Quick-fix brackets supplied for surface mounting. Mounting kits for conduit, chain suspension and catenary suspension are available as accessories. Wireless controlled via App with Bluetooth® 4.x - basicDIM Wireless Complete with 4000K LED.


Radio definition: basicDIM Wireless - Bluetooth® 4.x,
Radio frequency: 2.4 GHz, Radio power: +4 dBm.

ambient temperature: -20°C to +50°C

Dimensions: 735 x 180 x 95 mm
Luminaire input power: 26.2 W
Luminaire luminous flux: 4000 lm
Luminaire efficacy: 153 lm/W
Weight: 3.1 kg



TLG_FORL_F_PDBUNLIT.jpg



TLG_FORL_M_LED.wmf

This product contains a light source of energy efficiency class C.

ForceLED

92984182 FORCELED 4000 840 BC

THORN