


# ForceLED

# THORN

## 92987925 FORCELED 7000-840 MWBC



### ForceLED


A compact IP66, dust and moisture proof LED luminaire. Electronic, Luminaire with integral microwave motion sensor for on/off control via basicDIM Wireless (Bluetooth® 4.x). Class I electrical, IK10. Canopy: fully recyclable aluminium painted white. Diffuser: UV stabilised polycarbonate with linear prisms. Toggles: stainless steel. For surface, BESA or suspended mounting. Quick-fix brackets supplied for surface mounting. Mounting kits for conduit, chain suspension and catenary suspension are available as accessories. Complete with 4000K LED.

ambient temperature: -20°C to +40°C

Dimensions: 735 x 180 x 95 mm  
Luminaire input power: 53.2 W  
Luminaire luminous flux: 7000 lm  
Luminaire efficacy: 132 lm/W  
Weight: 3.1 kg



TLG\_FORL\_F\_PDBUNLIT.jpg



TLG\_FORL\_M\_LED.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

**ForceLED**

**92987925 FORCELED 7000-840 MWBC**

**THORN**