

Chalice 3

92989203 CHAL3 150 2000-830 EHF RSB

IEC EN 60598-1 RG 1	UK CA	X	IP20 ↑ IP54	halogen	IK09		CE			850°C	T _a 25	
---------------------	-------	---	----------------	---------	------	--	----	--	--	-------	-------------------	--


Chalice 3

A highly efficient and sustainable LED downlight with low height. Suitable for mounting in ceiling thicknesses of 1 to 40 mm and Ø150mm cut-out with spring clips. Remote, pluggable, Fixed output LED driver with DC functionality, adjustable 50-100%, NFC configurable. Loop in - loop out possible. Body: die-cast aluminium for highly efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in satinbrite finish with wide beam. Class II electrical (this product is not earthed), IP54_IP20. Complete with 3000K LED

Dimensions: Ø174 x 94 mm
 Luminaire input power: 16.9 W
 Luminaire luminous flux: 1950 lm
 Luminaire efficacy: 115 lm/W
 Weight: 0.68 kg



TLG_CHAL3_F_150_RSB.jpg



TLG_CHAL3_M_EHF150.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
 © Thorn Lighting

Chalice 3

92989203 CHAL3 150 2000-830 EHF RSB

THORN