









Chalice 3

92989218 CHAL3 150 1400-830 HFIX RMB

IEC EN 60598-1 RG 1	UK CA				IK09						T _a 25	
---------------------	-------	---	---	---	------	---	---	---	---	---	-------------------	--


Chalice 3

A highly efficient and sustainable LED downlight with low height. Suitable for mounting in ceiling thicknesses of 1 to 40 mm and Ø150mm cut-out with spring clips. Remote, pluggable, DALI-2 dimmable LED driver with DC functionality, adjustable 15-100%, NFC configurable, SwitchDIM compatible. Loop in - loop out possible. Body: die-cast aluminium for highly efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in high glossy finish for improved glare control in office applications. Class II electrical (this product is not earthed), IP54_IP20. Complete with 3000K LED

Dimensions: Ø174 x 94 mm
Luminaire input power: 12.2 W
Luminaire luminous flux: 1421 lm
Luminaire efficacy: 117 lm/W
Weight: 0.69 kg



TLG_CHAL3_F_150_RMB_IP54.jpg



TLG_CHAL3_M_EHF150.wmf

This product contains a light source of energy efficiency class D.

Chalice 3

92989218 CHAL3 150 1400-830 HFIX RMB

THORN