

Chalice 3

THORN

92989421 CHAL3 200 5000-830 EHF WFL RSB

IEC EN 60598-1 RG 1	UK CA	X	IP20	halogen	IK07		CE			850°C	T _a 25	
------------------------	----------	---	------	---------	------	--	----	--	--	-------	-------------------	--

Chalice 3

A high efficient and sustainable LED downlight for high ceiling application with wide flood beam (44°). Suitable for mounting in Ø200mm cut-out with spring clips. Remote, pluggable, Fixed output LED driver with DC functionality, adjustable 50-100%, NFC configurable. Loop in - loop out possible. Body: die-cast aluminium for high efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in satinbrite finish. Class II electrical (this product is not earthed), IP20. Complete with 3000K LED

Installation in concrete ceilings not permitted.

Dimensions: Ø223 x 134 mm
Luminaire input power: 44.1 W
Luminaire luminous flux: 5485 lm
Luminaire efficacy: 124 lm/W
Weight: 1.39 kg



TLG_CHAL3_F_200HC_RSB.jpg



TLG_CHAL3_M_EHF200HC.wmf

This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting