

Chalice 3

93900866 CHAL3 200 2000-840 HFIX E3 RSB

IEC EN 60598-1 RG 1	UK CA	X	IP20 ↑ IP54	halogen	IK09		CE			850°C	T _a 25	
---------------------	-------	---	----------------	---------	------	--	----	--	--	-------	-------------------	--


Chalice 3

A high efficient and sustainable LED downlight with low height. Suitable for mounting in ceiling thicknesses of 1 to 40 mm and Ø200mm cut-out with spring clips. Remote, pluggable, DALI-2 dimmable LED driver NFC configurable, SwitchDIM compatible with 3 hour, manual test, emergency lighting circuit. Body: die-cast aluminium for high efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in satinbrite finish with wide beam. Class II electrical (this product is not earthed), IP54_IP20. Complete with 4000K LED

Dimensions: Ø223 x 96 mm
 Luminaire input power: 17.4 W
 Luminaire luminous flux: 1990 lm
 Luminaire efficacy: 114 lm/W
 Weight: 1.39 kg



TLG_CHAL3_F_200_RSB_EM.jpg



TLG_CHAL3_M_EHF200.wmf

This product contains a light source of energy efficiency class B.