

Chalice 3

93901017 CHAL3 100 800-830 HFIX E3 RSB

IEC EN 60598-1 RG 1	UK CA	IP20	halogen	IK08	CE	850°C	T _a 25	
---------------------	-------	------	---------	------	----	-------	-------------------	--


Chalice 3

A high efficient and sustainable LED downlight with low height. Suitable for mounting in ceiling thicknesses of 1 to 40 mm and Ø100mm cut-out with spring clips. Remote, pluggable, DALI-2 dimmable LED driver NFC configurable, SwitchDIM compatible with 3 hour, manual test, emergency lighting circuit. Body: die-cast aluminium for high efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in satinbrite finish with wide beam. Class II electrical (this product is not earthed), IP54_IP20. Complete with 3000K LED

Dimensions: Ø119 x 75 mm
 Luminaire input power: 10.2 W
 Luminaire luminous flux: 740 lm
 Luminaire efficacy: 73 lm/W
 Weight: 0.86 kg



TLG_CHAL3_F_100_RSB_EM.jpg



TLG_CHAL3_M_EHF100L.wmf

Chalice 3

93901017 CHAL3 100 800-830 HFIX E3 RSB

THORN