

Chalice 3

93901048 CHAL3 150 1400-830 EHF E3 RSB

| | | | | | | | | | | | | |
|---------------------|-------|---|----------------|---------|------|--|----|--|--|-------|-------------------|--|
| IEC EN 60598-1 RG 1 | UK CA | X | IP20 ↑ IP54 | halogen | IK09 | | CE | | | 850°C | T _a 25 | |
|---------------------|-------|---|----------------|---------|------|--|----|--|--|-------|-------------------|--|

Chalice 3

A high efficient and sustainable LED downlight with low height. Suitable for mounting in ceiling thicknesses of 1 to 40 mm and Ø150mm cut-out with spring clips. Remote, pluggable, Fixed output LED driver NFC configurable with 3 hour, manual test, emergency lighting circuit. Body: die-cast aluminium for high efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in satinbrite finish with wide beam. Class II electrical (this product is not earthed), IP54_IP20. Complete with 3000K LED

Dimensions: Ø174 x 94 mm
 Luminaire input power: 15.4 W
 Luminaire luminous flux: 1340 lm
 Luminaire efficacy: 87 lm/W
 Weight: 1.13 kg



TLG_CHAL3_F_150_RSB_EM.jpg



TLG_CHAL3_M_EHF150.wmf

This product contains a light source of energy efficiency class D.