


Chalice 3

93901266 CHAL3 150 2000-840 HFIX E3D RMB




Chalice 3

A high efficient and sustainable LED downlight with low height. Suitable for mounting in ceiling thicknesses of 1 to 40 mm and Ø150mm cut-out with spring clips. Remote, pluggable, DALI-2 dimmable LED driver NFC configurable, SwitchDIM compatible with 3 hour, Self/DALI Addressable test, emergency lighting circuit. Body: die-cast aluminium for high efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in high glossy finish for improved glare control in office applications. Class II electrical (this product is not earthed), IP54_IP20. Complete with 4000K LED

Dimensions: Ø174 x 94 mm
 Luminaire input power: 19.5 W
 Luminaire luminous flux: 2172 lm
 Luminaire efficacy: 111 lm/W
 Weight: 1.14 kg



TLG_CHAL3_F_150_RMB_IP54_EMG.jpg



TLG_CHAL3_M_EHF150.wmf

This product contains a light source of energy efficiency class B.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Chalice 3

93901266 CHAL3 150 2000-840 HFIX E3D RMB

THORN