

## Chalice 3

93901268 CHAL3 150 3000-840 HFIX E3 RMB

IEC EN 60598-1 RG 1	UK CA				halogen	IK09					850°C	T <sub>a</sub> 25	
------------------------	----------	--	--	--	---------	------	--	--	--	--	-------	-------------------	--

### Chalice 3


A high efficient and sustainable LED downlight with low height. Suitable for mounting in ceiling thicknesses of 1 to 40 mm and Ø150mm cut-out with spring clips. Remote, pluggable, DALI-2 dimmable LED driver NFC configurable, SwitchDIM compatible with 3 hour, manual test, emergency lighting circuit. Body: die-cast aluminium for high efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in high glossy finish for improved glare control in office applications. Class II electrical (this product is not earthed), IP54\_IP20. Complete with 4000K LED

Installation in concrete ceilings not permitted.

Dimensions: Ø174 x 94 mm  
 Luminaire input power: 30.2 W  
 Luminaire luminous flux: 3343 lm  
 Luminaire efficacy: 111 lm/W  
 Weight: 1.14 kg



TLG\_CHAL3\_F\_150\_RMB\_IP54\_EMG.jpg



TLG\_CHAL3\_M\_EHF150.wmf

This product contains a light source of energy efficiency class B.

## Chalice 3

93901268 CHAL3 150 3000-840 HFIX E3 RMB

THORN