

## Chalice 3

93901315 CHAL3 200 3000-830 HFIX E3 RSB

IEC EN 60598-1 RG 1	UK CA	IP20	halogen	IK09	CE	850°C	T <sub>a</sub> 25	
---------------------	-------	------	---------	------	----	-------	-------------------	--

### Chalice 3


A high efficient and sustainable LED downlight with low height. Suitable for mounting in ceiling thicknesses of 1 to 40 mm and Ø200mm cut-out with spring clips. Remote, pluggable, DALI-2 dimmable LED driver NFC configurable, SwitchDIM compatible with 3 hour, manual test, emergency lighting circuit. Body: die-cast aluminium for high efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in satinbrite finish with wide beam. Class II electrical (this product is not earthed), IP54\_IP20. Complete with 3000K LED

Installation in concrete ceilings not permitted.

Dimensions: Ø223 x 96 mm  
 Luminaire input power: 26.6 W  
 Luminaire luminous flux: 2960 lm  
 Luminaire efficacy: 111 lm/W  
 Weight: 1.39 kg



TLG\_CHAL3\_F\_200\_RSB\_EM.jpg



TLG\_CHAL3\_M\_EHF200.wmf