

## Chalice 3

93901335 CHAL3 100 800-840 EHF E3 RSB

IEC EN 60598-1 RG 1	UK CA	IP20	IP54	halogen	IK08	CE	850°C	T <sub>a</sub> 25	
---------------------	-------	------	------	---------	------	----	-------	-------------------	--


### Chalice 3

A high efficient and sustainable LED downlight with low height. Suitable for mounting in ceiling thicknesses of 1 to 40 mm and Ø100mm cut-out with spring clips. Remote, pluggable, Fixed output LED driver NFC configurable with 3 hour, manual test, emergency lighting circuit. Body: die-cast aluminium for high efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in satinbrite finish with wide beam. Class II electrical (this product is not earthed), IP54\_IP20. Complete with 4000K LED

Dimensions: Ø119 x 75 mm  
 Luminaire input power: 10.6 W  
 Luminaire luminous flux: 771 lm  
 Luminaire efficacy: 73 lm/W  
 Weight: 0.86 kg



TLG\_CHAL3\_F\_100\_RSB\_EM.jpg



TLG\_CHAL3\_M\_EHF100L.wmf

This product contains a light source of energy efficiency class C.